



Enhancing the electro-mechanical properties of polydimethylsiloxane elastomers through blending with poly(dimethylsiloxane-co-methylphenylsiloxane) copolymers Acknowledgments

Yu, Liyun; Jeppe Madsen, Peter; Boucher, Sarah ; Skov, Anne Ladegaard

Publication date:
2018

Document Version
Peer reviewed version

[Link back to DTU Orbit](#)

Citation (APA):

Yu, L. (Author), Jeppe Madsen, P. (Author), Boucher, S. (Author), & Skov, A. L. (Author). (2018). Enhancing the electro-mechanical properties of polydimethylsiloxane elastomers through blending with poly(dimethylsiloxane-co-methylphenylsiloxane) copolymers Acknowledgments. Sound/Visual production (digital)

General rights

Copyright and moral rights for the publications made accessible in the public portal are retained by the authors and/or other copyright owners and it is a condition of accessing publications that users recognise and abide by the legal requirements associated with these rights.

- Users may download and print one copy of any publication from the public portal for the purpose of private study or research.
- You may not further distribute the material or use it for any profit-making activity or commercial gain
- You may freely distribute the URL identifying the publication in the public portal


If you believe that this document breaches copyright please contact us providing details, and we will remove access to the work immediately and investigate your claim.




2.2.14

Enhancing the electro-mechanical properties of polydimethylsiloxane elastomers through blending with poly(dimethylsiloxane-co-methylphenylsiloxane) copolymers


Liyun Yu, Peter Jeppe Madsen, Sarah Boucher, Anne Ladegaard Skov*
Technical University of Denmark, Danish Polymer Centre
al@kt.dtu.dk




Electrical treeing




Failure of insulation material




Phenyl group -
electron-trapping effect





Disturbance of cloud of π -
electrons - anion radicals



Voltage stabiliser




Anionic Ring-Opening Polymerisation



PDT_ba

$$a+b = 1$$

$$a=0.25, 0.50, 0.75$$



PDO_7525

Phenyl-PDMS copolymer in PDMS matrix

Thank you

Fig. 4 Cross-linked elastomer consisting of phenyl-PDMS in PDMS matrix and structures of the aced phenyl-PDMS copolymers.

concentration for the investigated elastomers at room temperature.

(a) Dielectric permittivity at a frequency of 0.1 Hz; (b) Dielectric loss at a frequency of 0.1 Hz; (c) Dielectric breakdown strength.

(d) Tensile strength at break; (e) Strain at break under tensile testing conditions; (f) Tensile strength; (g) Strain at break under tear testing conditions; (h) Young's modulus at 5% strain.